

Package ‘giscoR’

June 30, 2023

Type Package

Title Download Map Data from GISCO API - Eurostat

Version 0.3.5

Description Tools to download data from the GISCO (Geographic Information System of the Commission) Eurostat database <<https://ec.europa.eu/eurostat/web/gisco>>. Global and European map data available. This package is in no way officially related to or endorsed by Eurostat.

License GPL-3

URL <https://ropengov.github.io/giscoR/>,
<https://github.com/rOpenGov/giscoR>

BugReports <https://github.com/rOpenGov/giscoR/issues>

Depends R (>= 3.6.0)

Imports countrycode (>= 1.2.0), geojsonsf (>= 2.0.0), rappdirs (>= 0.3.0), sf (>= 0.9.0), utils

Suggests eurostat, ggplot2 (>= 3.0.0), knitr, lwgeom (>= 0.2-2), rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

Config/testthat/edition 3

Config/testthat/parallel false

Copyright General Copyright © European Union, 1995 - today. See file COPYRIGHTS for specific provisions.

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

X-schema.org-applicationCategory cartography

X-schema.org-isPartOf <http://ropengov.org/>

X-schema.org-keywords ropengov, r, spatial, api-wrapper, rstats, r-package, eurostat, gisco, thematic-maps, eurostat-data

NeedsCompilation no

Author Diego Hernangómez [aut, cre, cph]

(<<https://orcid.org/0000-0001-8457-4658>>, rOpenGov),

EuroGeographics [cph] (for the administrative boundaries.),

Vincent Arel-Bundock [cph] (<<https://orcid.org/0000-0003-2042-7063>>,
for the gisco_countrycode dataset.)

Maintainer Diego Hernangómez <diego.hernangomezherrero@gmail.com>

Repository CRAN

Date/Publication 2023-06-30 19:30:02 UTC

R topics documented:

gisco_attributions	2
gisco_bulk_download	4
gisco_check_access	6
gisco_clear_cache	6
gisco_coastallines	7
gisco_countries	8
gisco_countrycode	9
gisco_detect_cache_dir	10
gisco_get_airports	11
gisco_get_coastallines	13
gisco_get_countries	15
gisco_get_grid	17
gisco_get_healthcare	20
gisco_get_lau	22
gisco_get_nuts	25
gisco_get_postalcodes	27
gisco_get_units	29
gisco_get_urban_audit	32
gisco_nuts	34
gisco_set_cache_dir	35
tgs00026	36

Index 38

gisco_attributions *Attribution when publishing GISCO data*

Description

Get the legal text to be used along with the data downloaded with this package

Usage

```
gisco_attributions(lang = "en", copyright = FALSE)
```

Arguments

lang	Language (two-letter ISO code). See https://en.wikipedia.org/wiki/List_of_ISO_639-1_codes and Details.
copyright	Boolean. Whether to display the copyright notice or not on the console.

Details

Current languages supported are:

- "en" - English
- "da" - Danish
- "de" - German
- "es" - Spanish
- "fi" - Finish
- "fr" - French
- "no" - Norwegian
- "sv" - Swedish

Please consider [contributing](#) if you spot any mistake or want to add a new language.

Value

A string with the attribution to be used.

Note

COPYRIGHT NOTICE

When data downloaded from GISCO is used in any printed or electronic publication, in addition to any other provisions applicable to the whole Eurostat website, data source will have to be acknowledged in the legend of the map and in the introductory page of the publication with the following copyright notice:

- EN: (C) EuroGeographics for the administrative boundaries
- FR: (C) EuroGeographics pour les limites administratives
- DE: (C) EuroGeographics bezüglich der Verwaltungsgrenzen

For publications in languages other than English, French or German, the translation of the copyright notice in the language of the publication shall be used.

If you intend to use the data commercially, please contact EuroGeographics for information regarding their licence agreements.

Examples

```
gisco_attributions()
```

```
gisco_attributions(lang = "es", copyright = TRUE)
```

```
gisco_attributions(lang = "XXX")
```

gisco_bulk_download *Bulk download from GISCO API*

Description

Downloads zipped data from GISCO and extract them on the cache_dir folder.

Usage

```
gisco_bulk_download(
  id_giscoR = c("countries", "coastallines", "communes", "lau", "nuts", "urban_audit"),
  year = "2016",
  cache_dir = NULL,
  update_cache = FALSE,
  verbose = FALSE,
  resolution = "10",
  ext = c("geojson", "shp", "svg", "json", "gdb"),
  recursive = TRUE
)
```

Arguments

id_giscoR	Type of dataset to be downloaded. Values supported are: <ul style="list-style-type: none"> • "coastallines" • "communes" • "countries" • "lau" • "nuts" • "urban_audit"
year	Release year of the file. See Details
cache_dir	A path to a cache directory. See About caching .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source .geojson file.
verbose	Logical, displays information. Useful for debugging, default is FALSE.
resolution	Resolution of the geospatial data. One of <ul style="list-style-type: none"> • "60": 1:60million • "20": 1:20million • "10": 1:10million • "03": 1:3million • "01": 1:1million
ext	Extension of the file(s) to be downloaded. Formats available are "geojson", "shp", "svg", "json", "gdb". See Details .
recursive	Tries to unzip recursively the zip files (if any) included in the initial bulk download (case of ext = "shp").

Details

See the years available in the corresponding functions:

- [gisco_get_coastallines\(\)](#)
- [gisco_get_communes\(\)](#)
- [gisco_get_countries\(\)](#)
- [gisco_get_lau\(\)](#)
- [gisco_get_nuts\(\)](#)
- [gisco_get_urban_audit\(\)](#)

The usual extension used across **giscoR** is "geojson", however other formats are already available on GISCO.

Value

Silent function.

About caching

You can set your cache_dir with [gisco_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting update_cache = TRUE.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your cache_dir. Use the option verbose = TRUE for debugging the API query.

For a complete list of files available check [gisco_db](#).

Source

<https://gisco-services.ec.europa.eu/distribution/v2/>

See Also

Other political: [gisco_get_coastallines\(\)](#), [gisco_get_countries\(\)](#), [gisco_get_lau\(\)](#), [gisco_get_nuts\(\)](#), [gisco_get_postalcodes\(\)](#), [gisco_get_units\(\)](#), [gisco_get_urban_audit\(\)](#)

Examples

```
## Not run:  
  
# Countries 2016 - It would take some time  
gisco_bulk_download(id_giscoR = "countries", resolution = "60")  
  
## End(Not run)
```

gisco_check_access *Check access to GISCO API*

Description

Check if R has access to resources at <https://gisco-services.ec.europa.eu/distribution/v2/>.

Usage

```
gisco_check_access()
```

Value

a logical.

Examples

```
gisco_check_access()
```

gisco_clear_cache *Clear your **giscoR** cache dir*

Description

Use this function with caution. This function would clear your cached data and configuration, specifically:

- Deletes the **giscoR** config directory (`rappdirs::user_config_dir("giscoR", "R")`).
- Deletes the `cache_dir` directory.
- Deletes the values on stored on `Sys.getenv("GISCO_CACHE_DIR")` and `options(gisco_cache_dir)`.

Usage

```
gisco_clear_cache(config = FALSE, cached_data = TRUE, verbose = FALSE)
```

Arguments

<code>config</code>	if TRUE, will delete the configuration folder of giscoR .
<code>cached_data</code>	If this is set to TRUE, it will delete your <code>cache_dir</code> and all its content.
<code>verbose</code>	Logical, displays information. Useful for debugging, default is FALSE.

Details

This is an overkill function that is intended to reset your status as if you would never have installed and/or used **giscoR**.

Value

Invisible. This function is called for its side effects.

See Also

Other cache utilities: [gisco_detect_cache_dir\(\)](#), [gisco_set_cache_dir\(\)](#)

Examples

```
# Don't run this! It would modify your current state
## Not run:
gisco_clear_cache(verbose = TRUE)

Sys.getenv("GISCO_CACHE_DIR")

# Set new cache on a temp dir
newcache <- file.path(tempdir(), "giscoR", "pkgdown")

newcache

gisco_set_cache_dir(newcache)

Sys.getenv("GISCO_CACHE_DIR")

## End(Not run)
```

`gisco_coastallines` *World coastal lines POLYGON object*

Description

A sf object as provided by GISCO (2016 version).

Format

A POLYGON data frame (resolution: 1:20million, EPSG:4326) object with 3 variables:

- **FID**
- **COAS_ID**
- **geometry**: geometry field

Source

COAS_RG_20M_2016_4326.geojson file.

See Also

[gisco_get_coastallines\(\)](#)

Other dataset: [gisco_countries](#), [gisco_countrycode](#), [gisco_nuts](#), [tgs00026](#)

Examples

```
coasts <- gisco_coastallines

library(ggplot2)

ggplot(coasts) +
  geom_sf(color = "blue", fill = "blue", alpha = 0.2) +
  # Zoom on Oceania
  coord_sf(
    xlim = c(96, 179),
    ylim = c(-51, 11)
  ) +
  theme_minimal() +
  theme(
    plot.background = element_rect(
      fill = "black",
      color = "black"
    ),
    panel.grid = element_blank(),
    axis.text = element_text(colour = "grey90")
  )
```

gisco_countries

World countries POLYGON object

Description

A sf object including all countries as provided by GISCO (2016 version).

Format

A MULTIPOLYGON data frame (resolution: 1:20million, EPSG:4326) object with 257 rows and 7 variables:

- **id**: row ID
- **CNTR_NAME**: Official country name on local language
- **ISO3_CODE**: ISO 3166-1 alpha-3 code of each country, as provided by GISCO
- **CNTR_ID**: Country ID

- **NAME_ENGL**: Country name in English
- **FID**: FID
- **geometry**: geometry field

Source

[CNTR_RG_20M_2016_4326](#).geojson file.

See Also

[gisco_get_countries\(\)](#)

Other dataset: [gisco_coastallines](#), [gisco_countrycode](#), [gisco_nuts](#), [tgs00026](#)

Examples

```
cntry <- gisco_countries
GBR <- subset(cntry, ISO3_CODE == "GBR")

library(ggplot2)

ggplot(GBR) +
  geom_sf(color = "red3", fill = "blue4") +
  theme_void()
```

gisco_countrycode

Dataframe with different country code schemes and world regions

Description

A dataframe containing conversions between different country code schemes (Eurostat/ISO2 and 3) as well as geographic regions as provided by the World Bank and the UN (M49). This dataset is extracted from **countrycode** package.

Format

A data frame object with 249 rows and 12 variables:

- **CNTR_CODE**: Eurostat code of each country
- **iso2c**: ISO 3166-1 alpha-2 code of each country
- **ISO3_CODE**: ISO 3166-1 alpha-3 code of each country
- **iso.name.en**: ISO English short name
- **cldr.short.en**: English short name as provided by the Unicode Common Locale Data Repository <https://cldr.unicode.org/translation/displaynames/countryregion-territory-names>
- **continent**: As provided by the World Bank
- **un.region.code**: Numeric region code UN (M49)

- **un.region.name**: Region name UN (M49)
- **un.regionintermediate.code**: Numeric intermediate Region code UN (M49)
- **un.regionintermediate.name**: Intermediate Region name UN (M49)
- **un.regionsub.code**: Numeric sub-region code UN (M49)
- **un.regionsub.name**: Sub-Region name UN (M49)
- **eu**: Logical indicating if the country belongs to the European Union as per February 2021.

Source

[countrycode::codelist v1.2.0](#).

See Also

[gisco_get_countries\(\)](#), [countrycode::codelist](#), [countrycode::countrycode-package](#)

Other dataset: [gisco_coastallines](#), [gisco_countries](#), [gisco_nuts](#), [tgs00026](#)

Examples

```
data(gisco_countrycode)
```

gisco_detect_cache_dir

Helper function to detect current cache_dir

Description

Detect the path to your current cache_dir. See [gisco_set_cache_dir\(\)](#)

Usage

```
gisco_detect_cache_dir(...)
```

Arguments

... Ignored

Value

The path to the cache_dir used in this session

See Also

[gisco_set_cache_dir\(\)](#)

Other cache utilities: [gisco_clear_cache\(\)](#), [gisco_set_cache_dir\(\)](#)

Examples

```
gisco_detect_cache_dir()
```

```
gisco_get_airports    Get location of airports and ports from GISCO API
```

Description

Loads a sf object from GISCO API or your local library.

Usage

```
gisco_get_airports(  
  year = "2013",  
  country = NULL,  
  cache_dir = NULL,  
  update_cache = FALSE,  
  verbose = FALSE  
)
```

```
gisco_get_ports(  
  year = "2013",  
  country = NULL,  
  cache_dir = NULL,  
  update_cache = FALSE,  
  verbose = FALSE  
)
```

Arguments

year	Year of reference. Only year available right now is "2013".
country	Optional. A character vector of country codes. It could be either a vector of country names, a vector of ISO3 country codes or a vector of Eurostat country codes. Mixed types (as <code>c("Turkey", "US", "FRA")</code>) would not work. See also countrycode::countrycode() .
cache_dir	A path to a cache directory. See About caching .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source .geojson file.
verbose	Logical, displays information. Useful for debugging, default is FALSE.

Details

`gisco_get_airports()` refer to Europe. All shapefiles provided in [EPSG:4326](#).

`gisco_get_ports()` adds a new field CNTR_ISO2 to the original data identifying the country of the port. Worldwide information available. The port codes are aligned with [UN/LOCODE](#) standard.

Value

A POINT object on EPSG:4326.

About caching

You can set your cache_dir with `gisco_set_cache_dir()`.

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting `update_cache = TRUE`.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your cache_dir. Use the option `verbose = TRUE` for debugging the API query.

For a complete list of files available check `gisco_db`.

Source

<https://ec.europa.eu/eurostat/web/gisco/geodata/reference-data/transport-networks>

See Also

Other infrastructure: `gisco_get_healthcare()`

Examples

```
library(sf)

Greece <- gisco_get_countries(country = "EL", resolution = "1")
AirP_GC <- gisco_get_airports(country = "EL")
AirP_GC <- st_transform(AirP_GC, st_crs(Greece))

library(ggplot2)

ggplot(Greece) +
  geom_sf(fill = "grey80") +
  geom_sf(data = AirP_GC, color = "blue") +
  labs(
    title = "Airports on Greece",
    shape = NULL,
    color = NULL,
    caption = gisco_attributions()
  )

#####
#           Plot ports           #
#####

ports <- gisco_get_ports()
```

```
coast <- gisco_get_coastallines(year = 2013)

# To Equal Earth projection :)

library(sf)
coast <- st_transform(coast, 8857)
ports <- st_transform(ports, st_crs(coast))

ggplot(coast) +
  geom_sf(fill = "#F6E1B9", color = "#0978AB") +
  geom_sf(data = ports, fill = "red", shape = 21) +
  theme_void() +
  theme(
    panel.background = element_rect(fill = "#C6ECFF"),
    panel.grid = element_blank(),
    plot.title = element_text(face = "bold", hjust = 0.5),
    plot.subtitle = element_text(face = "italic", hjust = 0.5)
  ) +
  labs(
    title = "Ports Worldwide", subtitle = "Year 2013",
    caption = "(c) European Union, 1995 - today"
  )
```

gisco_get_coastallines

Get GISCO coastlines sf polygons

Description

Downloads worldwide coastlines

Usage

```
gisco_get_coastallines(
  year = "2016",
  epsg = "4326",
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE,
  resolution = "20"
)
```

Arguments

year Release year. One of "2006", "2010", "2013" or "2016"

epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> • "4258": ETRS89 • "4326": WGS84 • "3035": ETRS89 / ETRS-LAEA • "3857": Pseudo-Mercator
cache	A logical whether to do caching. Default is TRUE. See About caching .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source .geojson file.
cache_dir	A path to a cache directory. See About caching .
verbose	Logical, displays information. Useful for debugging, default is FALSE.
resolution	Resolution of the geospatial data. One of <ul style="list-style-type: none"> • "60": 1:60million • "20": 1:20million • "10": 1:10million • "03": 1:3million • "01": 1:1million

Value

A sf POLYGON object.

About caching

You can set your cache_dir with [gisco_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting update_cache = TRUE.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your cache_dir. Use the option verbose = TRUE for debugging the API query.

For a complete list of files available check [gisco_db](#).

Note

Please check the download and usage provisions on [gisco_attributions\(\)](#).

Source

<https://gisco-services.ec.europa.eu/distribution/v2/>

See Also

[gisco_coastallines](#)

Other political: [gisco_bulk_download\(\)](#), [gisco_get_countries\(\)](#), [gisco_get_lau\(\)](#), [gisco_get_nuts\(\)](#), [gisco_get_postalcodes\(\)](#), [gisco_get_units\(\)](#), [gisco_get_urban_audit\(\)](#)

Examples

```
coast <- gisco_get_coastallines()

library(ggplot2)

ggplot(coast) +
  geom_sf(color = "#1278AB", fill = "#FDFBEA") +
  # Zoom on Caribe
  coord_sf(
    xlim = c(-99, -49),
    ylim = c(4, 30)
  ) +
  theme_minimal() +
  theme(panel.background = element_rect(fill = "#C7E7FB", color = "black"))
```

`gisco_get_countries` *Get GISCO world country sf polygons, points and lines*

Description

Returns world country polygons, lines and points at a specified scale, as provided by GISCO. Also, specific areas as Gibraltar or Antarctica are presented separately. The definition of country used on GISCO correspond roughly with territories with an official [ISO-3166](#) code.

Usage

```
gisco_get_countries(
  year = "2016",
  epsg = "4326",
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE,
  resolution = "20",
  spatialtype = "RG",
  country = NULL,
  region = NULL
)
```

Arguments

<code>year</code>	Release year of the file. One of "2001", "2006", "2010", "2013", "2016" or "2020".
<code>epsg</code>	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none">"4258": ETRS89

	<ul style="list-style-type: none"> • "4326": WGS84 • "3035": ETRS89 / ETRS-LAEA • "3857": Pseudo-Mercator
cache	A logical whether to do caching. Default is TRUE. See About caching .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source .geojson file.
cache_dir	A path to a cache directory. See About caching .
verbose	Logical, displays information. Useful for debugging, default is FALSE.
resolution	Resolution of the geospatial data. One of <ul style="list-style-type: none"> • "60": 1:60million • "20": 1:20million • "10": 1:10million • "03": 1:3million • "01": 1:1million
spatialtype	Type of geometry to be returned: <ul style="list-style-type: none"> • "BN": Boundaries - LINESTRING object. • "COASTL": coastlines - LINESTRING object. • "INLAND": inland boundaries - LINESTRING object. • "LB": Labels - POINT object. • "RG": Regions - MULTIPOLYGON/POLYGON object.
country	Optional. A character vector of country codes. It could be either a vector of country names, a vector of ISO3 country codes or a vector of Eurostat country codes. Mixed types (as c("Turkey", "US", "FRA")) would not work. See also countrycode::countrycode() .
region	Optional. A character vector of UN M49 region codes or European Union membership. Possible values are "Africa", "Americas", "Asia", "Europe", "Oceania" or "EU" for countries belonging to the European Union (as per 2021). See About world regions and gisco_countrycode

Value

A sf object specified by spatialtype.

About caching

You can set your cache_dir with [gisco_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting update_cache = TRUE.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your cache_dir. Use the option verbose = TRUE for debugging the API query.

For a complete list of files available check [gisco_db](#).

World Regions

Regions are defined as per the geographic regions defined by the UN (see <https://unstats.un.org/unsd/methodology/m49/>). Under this scheme Cyprus is assigned to Asia. You may use `region = "EU"` to get the EU members (reference date: 2021).

Note

Please check the download and usage provisions on [gisco_attributions\(\)](#).

Source

<https://gisco-services.ec.europa.eu/distribution/v2/>

See Also

[gisco_countrycode\(\)](#), [gisco_countries](#), [countrycode::countrycode\(\)](#)

Other political: [gisco_bulk_download\(\)](#), [gisco_get_coastallines\(\)](#), [gisco_get_lau\(\)](#), [gisco_get_nuts\(\)](#), [gisco_get_postalcodes\(\)](#), [gisco_get_units\(\)](#), [gisco_get_urban_audit\(\)](#)

Examples

```
cntries <- gisco_get_countries()

library(ggplot2)
ggplot(cntries) +
  geom_sf()

# Get a region

africa <- gisco_get_countries(region = "Africa")
ggplot(africa) +
  geom_sf(fill = "#078930", col = "white") +
  theme_minimal()
```

`gisco_get_grid`

Get grid cells covering covering Europe for various resolutions

Description

These datasets contain grid cells covering the European land territory, for various resolutions from 1km to 100km. Base statistics such as population figures are provided for these cells.

Usage

```
gisco_get_grid(  
  resolution = "20",  
  spatialtype = c("REGION", "POINT"),  
  cache_dir = NULL,  
  update_cache = FALSE,  
  verbose = FALSE  
)
```

Arguments

resolution	Resolution of the grid cells on kms. Available values are "1", "2", "5", "10", "20", "50", "100". See Details
spatialtype	Select one of "REGION" or "POINT".
cache_dir	A path to a cache directory. See About caching .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source .geojson file.
verbose	Logical, displays information. Useful for debugging, default is FALSE.

Details

Files are distributed on EPSG:3035.

The file sizes range is from 428Kb (resolution = "100") to 1.7Gb resolution = "1". For resolutions 1km and 2km you would need to confirm the download.

Value

A POLYGON/POINT object.

About caching

You can set your cache_dir with [gisco_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting update_cache = TRUE.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your cache_dir. Use the option verbose = TRUE for debugging the API query.

For a complete list of files available check [gisco_db](#).

Note

There are specific downloading provisions, please see <https://ec.europa.eu/eurostat/web/gisco/geodata/reference-data/grids>

Author(s)

dieghernan, <https://github.com/dieghernan/>

Source

<https://ec.europa.eu/eurostat/web/gisco/geodata/reference-data/grids>

Examples

```
grid <- gisco_get_grid(resolution = 20)

# If downloaded correctly proceed

if (!is.null(grid)) {
  grid$popdens <- grid$TOT_P_2011 / 20

  breaks <- c(
    0, 0.1, 100, 500, 1000, 2500, 5000, 10000,
    25000, max(grid$popdens) + 1
  )

  # Cut groups

  grid$popdens_cut <- cut(grid$popdens,
    breaks = breaks,
    include.lowest = TRUE
  )
  cut_labs <- prettyNum(breaks, big.mark = " ")[-1]
  cut_labs[1] <- "0"
  cut_labs[9] <- "> 25 000"

  pal <- c("black", hcl.colors(length(breaks) - 2,
    palette = "Spectral",
    alpha = 0.9
  ))

  library(ggplot2)

  ggplot(grid) +
    geom_sf(aes(fill = popdens_cut), color = NA, linewidth = 0) +
    coord_sf(
      xlim = c(2500000, 7000000),
      ylim = c(1500000, 5200000)
    ) +
    scale_fill_manual(
      values = pal, na.value = "black",
      name = "people per sq. kilometer",
      labels = cut_labs,
      guide = guide_legend(
        direction = "horizontal",
        keyheight = 0.5,
        keywidth = 2,
        title.position = "top",
```

```

        title.hjust = 0.5,
        label.hjust = .5,
        nrow = 1,
        byrow = TRUE,
        reverse = FALSE,
        label.position = "bottom"
    )
) +
theme_void() +
labs(
  title = "Population density in Europe",
  subtitle = "Grid: 20 km.",
  caption = gisco_attributions()
) +
theme(
  plot.background = element_rect(fill = "grey2"),
  plot.title = element_text(
    size = 18, color = "white",
    hjust = 0.5,
  ),
  plot.subtitle = element_text(
    size = 14,
    color = "white",
    hjust = 0.5,
    face = "bold"
  ),
  plot.caption = element_text(
    size = 9, color = "grey60",
    hjust = 0.5, vjust = 0,
    margin = margin(t = 5, b = 10)
  ),
  legend.text = element_text(
    size = 8,
    color = "white"
  ),
  legend.title = element_text(
    color = "white"
  ),
  legend.position = "bottom"
)
}

```

gisco_get_healthcare *Get locations of healthcare services in Europe.*

Description

The dataset contains information on main healthcare services considered to be 'hospitals' by Member States.

Usage

```
gisco_get_healthcare(  
  cache = TRUE,  
  update_cache = FALSE,  
  cache_dir = NULL,  
  verbose = FALSE,  
  country = NULL  
)
```

Arguments

cache	A logical whether to do caching. Default is TRUE. See About caching .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source .geojson file.
cache_dir	A path to a cache directory. See About caching .
verbose	Logical, displays information. Useful for debugging, default is FALSE.
country	Optional. A character vector of country codes. It could be either a vector of country names, a vector of ISO3 country codes or a vector of Eurostat country codes. Mixed types (as <code>c("Turkey", "US", "FRA")</code>) would not work. See also countrycode::countrycode() .

Details

Files are distributed on EPSG:4326. Metadata available on <https://gisco-services.ec.europa.eu/pub/healthcare/metadata.pdf>.

Value

A POINT object.

About caching

You can set your cache_dir with [gisco_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting update_cache = TRUE.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your cache_dir. Use the option verbose = TRUE for debugging the API query.

For a complete list of files available check [gisco_db](#).

Author(s)

dieghernan, <https://github.com/dieghernan/>

Source

<https://ec.europa.eu/eurostat/web/gisco/geodata/reference-data/healthcare-services>

See Also

[gisco_get_countries\(\)](#)

Other infrastructure: [gisco_get_airports\(\)](#)

Examples

```
health_BEL <- gisco_get_healthcare(country = "Belgium")
# If downloaded

if (!is.null(health_BEL)) {
  health_BEL[health_BEL$public_private == "", ]$public_private <- "unknown"

  BEL <- gisco_get_nuts(country = "Belgium", nuts_level = 2)

  library(ggplot2)

  ggplot(BEL) +
    geom_sf(fill = "white", color = "grey80") +
    geom_sf(
      data = health_BEL, aes(color = public_private),
      alpha = 0.5, size = 3
    ) +
    theme_bw() +
    labs(
      title = "Healthcare in Belgium",
      subtitle = "NUTS 2",
      fill = "type",
      caption = paste0(gisco_attributions())
    ) +
    scale_color_manual(name = "type", values = hcl.colors(3, "Berlin")) +
    theme_minimal()
}
```

gisco_get_lau

Get GISCO urban areas sf polygons, points and lines

Description

[gisco_get_communes\(\)](#) and [gisco_get_lau\(\)](#) download shapes of Local Urban Areas, that correspond roughly with towns and cities.

Usage

```

gisco_get_communes(
  year = "2016",
  epsg = "4326",
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE,
  spatialtype = "RG",
  country = NULL
)

gisco_get_lau(
  year = "2016",
  epsg = "4326",
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE,
  country = NULL,
  gisco_id = NULL
)

```

Arguments

year	Release year of the file. See Details.
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> • "4258": ETRS89 • "4326": WGS84 • "3035": ETRS89 / ETRS-LAEA • "3857": Pseudo-Mercator
cache	A logical whether to do caching. Default is TRUE. See About caching .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source .geojson file.
cache_dir	A path to a cache directory. See About caching .
verbose	Logical, displays information. Useful for debugging, default is FALSE.
spatialtype	Type of geometry to be returned: <ul style="list-style-type: none"> • "BN": Boundaries - LINESTRING object. • "COASTL": coastlines - LINESTRING object. • "INLAND": inland boundaries - LINESTRING object. • "LB": Labels - POINT object. • "RG": Regions - MULTIPOLYGON/POLYGON object.
country	Optional. A character vector of country codes. It could be either a vector of country names, a vector of ISO3 country codes or a vector of Eurostat country codes. Mixed types (as c("Turkey", "US", "FRA")) would not work. See also countrycode::countrycode() .

`gisco_id` Optional. A character vector of GISCO_ID LAU values.

Details

Valid years for each function are:

- `gisco_get_communes`: one of '2001', '2004', '2006', '2008', '2010', '2013' or '2016'.
- `gisco_get_lau`: one of '2011', '2012', '2013', '2014', '2015', '2016', '2017', '2018', '2019', '2020'.

Value

A sf object specified by `spatialtype`. In the case of `gisco_get_lau()`, a POLYGON object.

About caching

You can set your `cache_dir` with `gisco_set_cache_dir()`.

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting `update_cache = TRUE`.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your `cache_dir`. Use the option `verbose = TRUE` for debugging the API query.

For a complete list of files available check `gisco_db`.

Note

Please check the download and usage provisions on `gisco_attributions()`.

See Also

Other political: `gisco_bulk_download()`, `gisco_get_coastlines()`, `gisco_get_countries()`, `gisco_get_nuts()`, `gisco_get_postalcodes()`, `gisco_get_units()`, `gisco_get_urban_audit()`

Examples

```
ire_lau <- gisco_get_communes(spatialtype = "LB", country = "Ireland")

if (!is.null(ire_lau)) {
  library(ggplot2)

  ggplot(ire_lau) +
    geom_sf(shape = 21, col = "#009A44", size = 0.5) +
    labs(
      title = "Communes in Ireland",
      subtitle = "Year 2016",
      caption = gisco_attributions()
    ) +
```



```
theme_void() +  
theme(text = element_text(  
  colour = "#009A44",  
  family = "serif", face = "bold"  
))  
}
```

`gisco_get_nuts`*Get GISCO NUTS sf polygons, points and lines*

Description

Returns **NUTS regions** polygons, lines and points at a specified scale, as provided by GISCO.

NUTS are provided at three different levels:

- "0": Country level
- "1": Groups of states/regions
- "2": States/regions
- "3": Counties/provinces/districts

Note that NUTS-level definition may vary across countries. See also <https://ec.europa.eu/eurostat/web/nuts/background>.

Usage

```
gisco_get_nuts(  
  year = "2016",  
  epsg = "4326",  
  cache = TRUE,  
  update_cache = FALSE,  
  cache_dir = NULL,  
  verbose = FALSE,  
  resolution = "20",  
  spatialtype = "RG",  
  country = NULL,  
  nuts_id = NULL,  
  nuts_level = "all"  
)
```

Arguments

- | | |
|-------------------|--|
| <code>year</code> | Release year of the file. One of "2003", "2006", "2010", "2013", "2016" or "2021". |
| <code>epsg</code> | projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none">• "4258": ETRS89 |

	<ul style="list-style-type: none"> • "4326": WGS84 • "3035": ETRS89 / ETRS-LAEA • "3857": Pseudo-Mercator
cache	A logical whether to do caching. Default is TRUE. See About caching .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source .geojson file.
cache_dir	A path to a cache directory. See About caching .
verbose	Logical, displays information. Useful for debugging, default is FALSE.
resolution	Resolution of the geospatial data. One of <ul style="list-style-type: none"> • "60": 1:60million • "20": 1:20million • "10": 1:10million • "03": 1:3million • "01": 1:1million
spatialtype	Type of geometry to be returned: <ul style="list-style-type: none"> • "BN": Boundaries - LINESTRING object. • "LB": Labels - POINT object. • "RG": Regions - MULTIPOLYGON/POLYGON object.
country	Optional. A character vector of country codes. It could be either a vector of country names, a vector of ISO3 country codes or a vector of Eurostat country codes. Mixed types (as c("Turkey", "US", "FRA")) would not work. See also countrycode::countrycode() .
nuts_id	Optional. A character vector of NUTS IDs.
nuts_level	NUTS level. One of "0", "1", "2" or "3". See Description.

Value

A sf object specified by spatialtype.

About caching

You can set your cache_dir with [gisco_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting update_cache = TRUE.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your cache_dir. Use the option verbose = TRUE for debugging the API query.

For a complete list of files available check [gisco_db](#).

Source

<https://gisco-services.ec.europa.eu/distribution/v2/>

See Also

[gisco_nuts](#), [gisco_get_countries\(\)](#)

Other political: [gisco_bulk_download\(\)](#), [gisco_get_coastallines\(\)](#), [gisco_get_countries\(\)](#), [gisco_get_lau\(\)](#), [gisco_get_postalcodes\(\)](#), [gisco_get_units\(\)](#), [gisco_get_urban_audit\(\)](#)

Examples

```
nuts2 <- gisco_get_nuts(nuts_level = 2)

library(ggplot2)

ggplot(nuts2) +
  geom_sf() +
  # ETRS89 / ETRS-LAEA
  coord_sf(
    crs = 3035, xlim = c(2377294, 7453440),
    ylim = c(1313597, 5628510)
  ) +
  labs(title = "NUTS-2 levels")

# NUTS-3 for Germany
germany_nuts3 <- gisco_get_nuts(nuts_level = 3, country = "Germany")

ggplot(germany_nuts3) +
  geom_sf() +
  labs(
    title = "NUTS-3 levels",
    subtitle = "Germany",
    caption = gisco_attributions()
  )

# Select specific regions
select_nuts <- gisco_get_nuts(nuts_id = c("ES2", "FRJ", "FRL", "ITC"))

ggplot(select_nuts) +
  geom_sf(aes(fill = CNTR_CODE)) +
  scale_fill_viridis_d()
```

`gisco_get_postalcodes` *Get postal code points from GISCO*

Description

Get postal codes points of the EU, EFTA and candidate countries.

Usage

```
gisco_get_postalcodes(
  year = "2020",
  country = NULL,
  cache_dir = NULL,
  update_cache = FALSE,
  verbose = FALSE
)
```

Arguments

year	Year of reference. Currently only "2020" is available.
country	Optional. A character vector of country codes. It could be either a vector of country names, a vector of ISO3 country codes or a vector of Eurostat country codes. Mixed types (as c("Turkey", "US", "FRA")) would not work. See also countrycode::countrycode() .
cache_dir	A path to a cache directory. See About caching .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source .geojson file.
verbose	Logical, displays information. Useful for debugging, default is FALSE.

Details

The postal code point dataset shows the location of postal codes, NUTS codes and the Degree of Urbanisation classification across the EU, EFTA and candidate countries from a variety of sources. Its primary purpose is to create correspondence tables for the NUTS classification (EC) 1059/2003 as part of the Tercet Regulation (EU) 2017/2391

Value

A POINT object on EPSG:4326.

Copyright

The dataset is released under the CC-BY-SA-4.0 licence and requires the following attribution whenever used:

(c) European Union - GISCO, 2021, postal code point dataset, Licence CC-BY-SA 4.0 available at <https://ec.europa.eu/eurostat/web/gisco/geodata/reference-data>

Shapefiles provided in ETRS89 ([EPSG:4258](#)).

About caching

You can set your cache_dir with [gisco_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting update_cache = TRUE.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your cache_dir. Use the option verbose = TRUE for debugging the API query.

For a complete list of files available check [gisco_db](#).

Source

<https://ec.europa.eu/eurostat/web/gisco/geodata/reference-data/postal-codes>

See Also

Other political: [gisco_bulk_download\(\)](#), [gisco_get_coastallines\(\)](#), [gisco_get_countries\(\)](#), [gisco_get_lau\(\)](#), [gisco_get_nuts\(\)](#), [gisco_get_units\(\)](#), [gisco_get_urban_audit\(\)](#)

Examples

```
# Heavy-weight download!
## Not run:

pc_bel <- gisco_get_postalcodes(country = "BE")

if (!is.null(pc_bel)) {
  library(ggplot2)

  ggplot(pc_bel) +
    geom_sf(color = "gold") +
    theme_bw() +
    labs(
      title = "Postcodes of Belgium",
      subtitle = "2020",
      caption = paste("(c) European Union - GISCO, 2021,",
        "postal code point dataset",
        "Licence CC-BY-SA 4.0",
        sep = "\n"
      )
    )
}

## End(Not run)
```

gisco_get_units

Get geospatial units data from GISCO API

Description

Download individual shapefiles of units. Unlike [gisco_get_countries\(\)](#), [gisco_get_nuts\(\)](#) or [gisco_get_urban_audit\(\)](#), that downloads a full dataset and applies filters, [gisco_get_units\(\)](#) downloads a single shapefile for each unit.

Usage

```
gisco_get_units(
  id_giscoR = c("nuts", "countries", "urban_audit"),
  unit = "ES4",
  mode = c("sf", "df"),
  year = "2016",
  epsg = "4326",
  cache = TRUE,
  update_cache = FALSE,
  cache_dir = NULL,
  verbose = FALSE,
  resolution = "20",
  spatialtype = "RG"
)
```

Arguments

id_giscoR	Select the unit type to be downloaded. Accepted values are "nuts", "countries" or "urban_audit".
unit	Unit ID to be downloaded. See Details.
mode	Controls the output of the function. Possible values are "sf" or "df". See Value and Details.
year	Release year of the file. One of "2001", "2006", "2010", "2013", "2016" or "2020".
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> • "4258": ETRS89 • "4326": WGS84 • "3035": ETRS89 / ETRS-LAEA • "3857": Pseudo-Mercator
cache	A logical whether to do caching. Default is TRUE. See About caching .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source .geojson file.
cache_dir	A path to a cache directory. See About caching .
verbose	Logical, displays information. Useful for debugging, default is FALSE.
resolution	Resolution of the geospatial data. One of <ul style="list-style-type: none"> • "60": 1:60million • "20": 1:20million • "10": 1:10million • "03": 1:3million • "01": 1:1million
spatialtype	Type of geometry to be returned: "RG", for POLYGON and "LB" for POINT.

Details

The function can return a dataframe on mode = "df" or a sf object on mode = "sf".

In order to see the available unit ids with the required combination of spatialtype, year, first run the function on "df" mode. Once that you get the data frame you can select the required ids on the unit parameter.

On mode = "df" the only relevant parameters are spatialtype, year.

Value

A sf object on mode = "sf" or a dataframe on mode = "df".

About caching

You can set your cache_dir with [gisco_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting update_cache = TRUE.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your cache_dir. Use the option verbose = TRUE for debugging the API query.

For a complete list of files available check [gisco_db](#).

Note

Country-level files would be renamed on your cache_dir to avoid naming conflicts with NUTS-0 datasets.

Please check the download and usage provisions on [gisco_attributions\(\)](#).

Author(s)

dieghernan, <https://github.com/dieghernan/>

Source

<https://gisco-services.ec.europa.eu/distribution/v2/>

See Also

[gisco_get_countries\(\)](#)

Other political: [gisco_bulk_download\(\)](#), [gisco_get_coastallines\(\)](#), [gisco_get_countries\(\)](#), [gisco_get_lau\(\)](#), [gisco_get_nuts\(\)](#), [gisco_get_postalcodes\(\)](#), [gisco_get_urban_audit\(\)](#)

Examples

```
cities <- gisco_get_units(  
  id_giscoR = "urban_audit",  
  mode = "df",
```

```

    year = "2020"
  )
  VAL <- cities[grep("Valencia", cities$URAU_NAME), ]
  # Order from big to small
  VAL <- VAL[order(as.double(VAL$AREA_SQM), decreasing = TRUE), ]

  VAL.sf <- gisco_get_units(
    id_giscoR = "urban_audit",
    year = "2020",
    unit = VAL$URAU_CODE
  )
  # Provincia
  Provincia <-
    gisco_get_units(
      id_giscoR = "nuts",
      unit = c("ES523"),
      resolution = "01"
    )

  # Reorder
  VAL.sf$URAU_CATG <- factor(VAL.sf$URAU_CATG, levels = c("F", "K", "C"))

  # Plot
  library(ggplot2)

  ggplot(Provincia) +
    geom_sf(fill = "gray1") +
    geom_sf(data = VAL.sf, aes(fill = URAU_CATG)) +
    scale_fill_viridis_d() +
    labs(
      title = "Valencia",
      subtitle = "Urban Audit",
      fill = "Urban Audit\ncategory"
    )

```

`gisco_get_urban_audit` *Get GISCO greater cities and metropolitan areas sf polygons and points*

Description

Returns polygons and points corresponding to cities, greater cities and metropolitan areas included on the **Urban Audit report** of Eurostat.

Usage

```

gisco_get_urban_audit(
  year = "2020",

```



```

    epsg = "4326",
    cache = TRUE,
    update_cache = FALSE,
    cache_dir = NULL,
    verbose = FALSE,
    spatialtype = "RG",
    country = NULL,
    level = NULL
)

```

Arguments

year	Release year of the file. One of "2001", "2004", "2014", "2018" or "2020".
epsg	projection of the map: 4-digit EPSG code . One of: <ul style="list-style-type: none"> • "4258": ETRS89 • "4326": WGS84 • "3035": ETRS89 / ETRS-LAEA • "3857": Pseudo-Mercator
cache	A logical whether to do caching. Default is TRUE. See About caching .
update_cache	A logical whether to update cache. Default is FALSE. When set to TRUE it would force a fresh download of the source .geojson file.
cache_dir	A path to a cache directory. See About caching .
verbose	Logical, displays information. Useful for debugging, default is FALSE.
spatialtype	Type of geometry to be returned: <ul style="list-style-type: none"> • "LB": Labels - POINT object. • "RG": Regions - MULTIPOLYGON/POLYGON object.
country	Optional. A character vector of country codes. It could be either a vector of country names, a vector of ISO3 country codes or a vector of Eurostat country codes. Mixed types (as c("Turkey", "US", "FRA")) would not work. See also countrycode::countrycode() .
level	Level of Urban Audit. Possible values are "CITIES", "FUA", "GREATER_CITIES" or NULL, that would download the full dataset.

Value

A sf object specified by spatialtype.

About caching

You can set your cache_dir with [gisco_set_cache_dir\(\)](#).

Sometimes cached files may be corrupt. On that case, try re-downloading the data setting update_cache = TRUE.

If you experience any problem on download, try to download the corresponding .geojson file by any other method and save it on your cache_dir. Use the option verbose = TRUE for debugging the API query.

For a complete list of files available check [gisco_db](#).

Note

Please check the download and usage provisions on [gisco_attributions\(\)](#).

Source

<https://gisco-services.ec.europa.eu/distribution/v2/>

See Also

[gisco_get_communes\(\)](#), [gisco_get_lau\(\)](#)

Other political: [gisco_bulk_download\(\)](#), [gisco_get_coastallines\(\)](#), [gisco_get_countries\(\)](#), [gisco_get_lau\(\)](#), [gisco_get_nuts\(\)](#), [gisco_get_postalcodes\(\)](#), [gisco_get_units\(\)](#)

Examples

```
cities <- gisco_get_urban_audit(year = "2020", level = "CITIES")

if (!is.null(cities)) {
  bcn <- cities[cities$URAU_NAME == "Barcelona", ]

  library(ggplot2)
  ggplot(bcn) +
    geom_sf()
}
```

`gisco_nuts`

All NUTS POLYGON object

Description

A sf object including all NUTS levels as provided by GISCO (2016 version).

Format

A POLYGON data frame (resolution: 1:20million, EPSG:4326) object with 2,016 rows and 11 variables:

- **id**: row ID
- **COAST_TYPE**: COAST_TYPE
- **MOUNT_TYPE**: MOUNT_TYPE
- **NAME_LATN**: Name on Latin characters
- **CNTR_CODE**: Eurostat Country code
- **FID**: FID

- **NUTS_ID**: NUTS identifier
- **NUTS_NAME**: NUTS name on local alphabet
- **LEVL_CODE**: NUTS level code (0,1,2,3)
- **URBN_TYPE**: URBN_TYPE
- **geometry**: geometry field

Source

[NUTS_RG_20M_2016_4326.geojson](#) file.

See Also

[gisco_get_nuts\(\)](#)

Other dataset: [gisco_coastallines](#), [gisco_countries](#), [gisco_countrycode](#), [tgs00026](#)

Examples

```
nuts <- gisco_nuts

italy <- subset(nuts, CNTR_CODE == "IT" & LEVL_CODE == 3)

library(ggplot2)

ggplot(italy) +
  geom_sf()
```

`gisco_set_cache_dir` *Set your **giscoR** cache dir*

Description

This function will store your `cache_dir` path on your local machine and would load it for future sessions. Type `Sys.getenv("GISCO_CACHE_DIR")` to find your cached path.

Alternatively, you can store the `cache_dir` manually with the following options:

- Run `Sys.setenv(GISCO_CACHE_DIR = "cache_dir")`. You would need to run this command on each session (Similar to `install = FALSE`).
- Set `options(gisco_cache_dir = "cache_dir")`. Similar to the previous option. This is **not recommended any more**, and it is provided for backwards compatibility purposes.
- Write this line on your `.Renviron` file: `GISCO_CACHE_DIR = "value_for_cache_dir"` (same behavior than `install = TRUE`). This would store your `cache_dir` permanently.

Usage

```

gisco_set_cache_dir(
  cache_dir,
  overwrite = FALSE,
  install = FALSE,
  verbose = TRUE
)

```

Arguments

cache_dir	A path to a cache directory. On missing value the function would store the cached files on a temporary dir (See base::tempdir()).
overwrite	If this is set to TRUE, it will overwrite an existing GISCO_CACHE_DIR that you already have in local machine.
install	if TRUE, will install the key in your local machine for use in future sessions. Defaults to FALSE. If cache_dir is FALSE this parameter is set to FALSE automatically.
verbose	Logical, displays information. Useful for debugging, default is FALSE.

Value

An (invisible) character with the path to your cache_dir.

See Also

[rappdirs::user_config_dir\(\)](#)

Other cache utilities: [gisco_clear_cache\(\)](#), [gisco_detect_cache_dir\(\)](#)

Examples

```

# Don't run this! It would modify your current state
## Not run:
gisco_set_cache_dir(verbose = TRUE)

## End(Not run)

Sys.getenv("GISCO_CACHE_DIR")

```

Description

The disposable income of private households is the balance of primary income (operating surplus/mixed income plus compensation of employees plus property income received minus property income paid) and the redistribution of income in cash. These transactions comprise social contributions paid, social benefits in cash received, current taxes on income and wealth paid, as well as other current transfers. Disposable income does not include social transfers in kind coming from public administrations or non-profit institutions serving households.

Format

data_frame:

- **geo**: NUTS2 identifier
- **time**: reference year (2007 to 2018)
- **values**: value in euros

Source

<https://ec.europa.eu/eurostat>, extracted on 2020-10-27

See Also

Other dataset: [gisco_coastallines](#), [gisco_countries](#), [gisco_countrycode](#), [gisco_nuts](#)

Examples

```
data(tgs00026)
```

Index

- * **cache utilities**
 - [gisco_clear_cache](#), 6
 - [gisco_detect_cache_dir](#), 10
 - [gisco_set_cache_dir](#), 35
- * **dataset**
 - [gisco_coastallines](#), 7
 - [gisco_countries](#), 8
 - [gisco_countrycode](#), 9
 - [gisco_nuts](#), 34
 - [tgs00026](#), 36
- * **helper**
 - [gisco_attributions](#), 2
 - [gisco_check_access](#), 6
- * **infrastructure**
 - [gisco_get_airports](#), 11
 - [gisco_get_healthcare](#), 20
- * **misc**
 - [gisco_get_grid](#), 17
- * **political**
 - [gisco_bulk_download](#), 4
 - [gisco_get_coastallines](#), 13
 - [gisco_get_countries](#), 15
 - [gisco_get_lau](#), 22
 - [gisco_get_nuts](#), 25
 - [gisco_get_postalcodes](#), 27
 - [gisco_get_units](#), 29
 - [gisco_get_urban_audit](#), 32
- [base::tempdir\(\)](#), 36
- [countrycode::codelist](#), 10
- [countrycode::countrycode\(\)](#), 11, 16, 17, 21, 23, 26, 28, 33
- [countrycode::countrycode-package](#), 10
- [gisco_attributions](#), 2
- [gisco_attributions\(\)](#), 14, 17, 24, 31, 34
- [gisco_bulk_download](#), 4, 14, 17, 24, 27, 29, 31, 34
- [gisco_check_access](#), 6
- [gisco_clear_cache](#), 6, 10, 36
- [gisco_coastallines](#), 7, 9, 10, 14, 35, 37
- [gisco_countries](#), 8, 8, 10, 17, 35, 37
- [gisco_countrycode](#), 8, 9, 9, 16, 35, 37
- [gisco_countrycode\(\)](#), 17
- [gisco_db](#), 5, 12, 14, 16, 18, 21, 24, 26, 29, 31, 33
- [gisco_detect_cache_dir](#), 7, 10, 36
- [gisco_get_airports](#), 11, 22
- [gisco_get_airports\(\)](#), 11
- [gisco_get_coastallines](#), 5, 13, 17, 24, 27, 29, 31, 34
- [gisco_get_coastallines\(\)](#), 5, 8
- [gisco_get_communes \(gisco_get_lau\)](#), 22
- [gisco_get_communes\(\)](#), 5, 22, 34
- [gisco_get_countries](#), 5, 14, 15, 24, 27, 29, 31, 34
- [gisco_get_countries\(\)](#), 5, 9, 10, 22, 27, 29, 31
- [gisco_get_grid](#), 17
- [gisco_get_healthcare](#), 12, 20
- [gisco_get_lau](#), 5, 14, 17, 22, 27, 29, 31, 34
- [gisco_get_lau\(\)](#), 5, 22, 24, 34
- [gisco_get_nuts](#), 5, 14, 17, 24, 25, 29, 31, 34
- [gisco_get_nuts\(\)](#), 5, 29, 35
- [gisco_get_ports \(gisco_get_airports\)](#), 11
- [gisco_get_ports\(\)](#), 11
- [gisco_get_postalcodes](#), 5, 14, 17, 24, 27, 27, 31, 34
- [gisco_get_units](#), 5, 14, 17, 24, 27, 29, 29, 34
- [gisco_get_units\(\)](#), 29
- [gisco_get_urban_audit](#), 5, 14, 17, 24, 27, 29, 31, 32
- [gisco_get_urban_audit\(\)](#), 5, 29
- [gisco_nuts](#), 8–10, 27, 34, 37
- [gisco_set_cache_dir](#), 7, 10, 35
- [gisco_set_cache_dir\(\)](#), 5, 10, 12, 14, 16, 18, 21, 24, 26, 28, 31, 33
- [rappdirs::user_config_dir\(\)](#), 36

tgs00026, [8-10](#), [35](#), [36](#)